



FEATURES

- All aluminum construction
- Durable black powder coat finish
- Steel ball bearing glides
- Spring activated locking mechanism
- Hinged AC covers
- Pass thru connectivity
- One or two user drawers
- Standard computer interface connectivity
- No table penetration or modification
- Screw mounts under table for quick installation
- Standard and custom configurations
- Made in USA

The RCI Custom Products **MPD Series** Media Presentation Drawers allow for interconnectivity between PC's and various display devices from conference and boardroom tables without the need to penetrate or modify the table top. Designed as an easy to install gliding drawer, the MPD unit attaches quickly and easily with six mounting screws to the underside of almost any conference type table. Data and electrical connections are made with common "thru" type rear panel mount connectors, so the unit can be installed and ready for use in as little as 15 minutes, saving both time and money.

Available in single and dual user models, the standard MPD-1 front panel is factory equipped with one HD15 connector, one RJ45 CAT 6, one RJ11, one 3.5mm mini stereo audio, and one AC outlet. The standard MPD-2 dual-user front panel is equipped with two HD15 connectors, two RJ45 CAT 6, two RJ11, two 3.5mm mini stereo audio, and two AC outlets. Rear panels feed thru connectivity is provided for both units.

Custom configured MPD units are always available. Please contact factory for layout, pricing and delivery.

SPECIFICATIONS:**MPD-1 (single user)**

Dimensions: 7-5/16" W x 3" H x 11" D
Mounting Plate: 9" W x 11"
Connector Panel: 4-3/4" x 2-3/4"
Usable Area: 3-3/4" x 2-1/2"
Rear Panel: 3" x 7-3/8"
Usable Area: 2-3/4" x 6-1/4"
Weight: 4 lbs.
Connections: One- HD15, one- RJ45 CAT6,
one- RJ11, one- 3.5MM mini
stereo audio, one- AC outlet

MPD-2 (dual user)

Dimensions: 7-5/16" W x 3" H x 15" D
Mounting Plate: 9" W x 15"
Connector Panel: 4-7/8" x 6-3/4"
Usable Area: 3-3/4" x 6-1/4"
Rear Panel: 3" x 7-3/8"
Usable Area: 2-3/4" x 6-1/4"
Weight: 6 lbs.
Connections: Two- HD15, two- RJ45 CAT 6,
two- RJ11, two- 3.5mm mini
stereo audio, two- AC outlet



MPD-1 (Rear panel)



MPD-2 (Rear panel)

A & E SPECIFICATIONS

The media presentation drawer shall be RCI Custom Products Model _____ (MPD-1, MPD-2). Unit shall mount below table top with no more than 6 fasteners. The unit shall be fabricated and assembled as an aluminum drawer assembly with steel ball bearing glides and spring activated locking mechanism to prevent drawer from closing while in use. Units shall contain one HD15 (VGA), one RJ45 CAT-6 (data), one RJ11 (phone), one 3.5 mm mini stereo (audio), and one AC outlet (power). Should the MPD-2 (dual user) unit be required, provisions for the identical connector points shall be doubled. Rear panel connectors shall be "feed-thru" type. Units shall be finished with black textured powder coat. Dimensions shall be 7-5/16"W x 3"H x 11"D (MPD-1), or 7-5/16"W x 3"H x 15"D (MPD-2). The Unit shall be provided with UL listing.